

## NOTCH DETAIL

2" GRADE BOARD\_ NOTCHES (TYP)

2"x12" PRESSURE TREATED GRADE BOARD **VEGETATED** FLOW PATH. \*15% MAX FOR FLOW CONTROL/WATER SEE NOTE 1 QUALITY TREATMENT IN RURAL AREAS. 20% MAX.\* 15% MAX. GALVANIZED BOLT (TYP) 12" 36" WASHED DRAIN ROCK, SEE NOTE 3 4" (MIN) PERFORATED PVC UNDERDRAIN PIPE 6" (MIN)-PER WSDOT SPEC. 9-05.2(6), LAID LEVEL GEOTEXTILE, SEE NOTE 2 4"x4" PRESSURE TREATED SUPPORT POST **UNDISTURBED** NATIVE SOIL

## **GENERAL NOTES:**

 REFER TO THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM FOR SETBACK AND INFEASIBILITY REQUIREMENTS.

## NOTES:

- A VEGETATED FLOW PATH MUST BE PROVIDED IN ACCORDANCE THE 2017 CITY OF EDMONDS STORMWATER ADDENDUM REQUIREMENTS.
- 2. GEOTEXTILE SHALL CONFORM TO WSDOT SPEC. 9-33.2(1), GEOTEXTILE FOR SEPARATION, NON-WOVEN TYPE.
- 3. WASHED DRAIN ROCK SHALL CONFORM TO WSDOT SPEC. 9-03.12(5), GRAVEL BACKFILL FOR DRYWELLS.



## <u>CITY OF EDMONDS</u>

**SECTION** 

PUBLIC WORKS DEPARTMENT TYPICAL DISPERSION TRENCH WITH NOTCHED GRADE BOARD

APPROVED BY: R. ENGLISH

REVISION DATE
DECEMBER 2017

STANDARD DETAIL

SD - 632